

HILL  TOP[®]
Surfaces

Storie di
Milano

le pietre minerali

MILANO



IDYLIUM

DECLARATION OF PERFORMANCE

Nº. 002BS

12 mm

1. Identification code of the product type: dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$, thickness = 12 mm.
2. Inteded use (s): for floor ad walls, interior and exterior.
3. Name and contact address of the manufacturer:
BEST SURFACE S.L.
Carretera de Castellón 117 y DS Foyes 5D
12110 Alcora (Castellón), Spain
4. System (s) of assessment and verification of constancy of performance:
System 3 & 4
5. Name and identification number of notified laboratory:
Centro Ceramico, Laboratory nº 0058L, has conducted tests for the determination of lead and cadmium emissions, subject to system 3, and issued test reports No. 980/19 and No. 981/19 dated 2 March 2020.
6. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 / A1 _{FL}	EN 14411: 2016
Release of dangerous substance:		
- Cadmium	< 0,001 mg/dm ²	
- Lead	< 0,01 mg/dm ²	
Breaking strength	> 4000 N	
Adhesión for cementitious adhesive, type C2 S1/C2S2	> 1 N/mm ²	
Thermal shock resistance	Passed	
Durability for:		
- Interior use	Passed	
- Exterior use	Passed	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

BESTSURFACE
BREAKING DESIGN

Best Surface Holding Srl
Via Camperio Manfredo, 14
20123 Milano · Italy
Ph +39 02 58215360
Fax +39 02 58215368
P.IVA/C.F. 10463820968
REA MI-2533743
Cap. Soc. 250.000,00 Euro i.v.

Best Surface S.L.
Carretera de Castellón, 117
y DS Foyes 5 Den Partida
Foyes Ferraes
12110 Alcora · Castellón
NIF/VAT: B-44513752
Ph +34 964 78 45 45
Fax +34 964 78 45 00
Cap. Soc. 10.000.000 Euro i.v.

Headquarters
Via San Clemente 1
20122 Milano · Italy
Ph +39 02 50020754
Fax +39 02 50020764

idylium.com

Nº. 005BS

12 mm MESH

1. Identification code of the product type: dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$, thickness = 12 mm-mesh
2. Inteded use (s): for floor ad walls, interior and exterior.
3. Name and contact address of the manufacturer:
BEST SURFACE S.L.
Carretera de Castellón 117 y DS Foyes 5D
12110 Alcora (Castellón), Spain
4. System (s) of assessment and verification of constancy of performance:
System 3 & 4
5. Name and identification number of notified laboratory:
Centro Ceramico, Laboratory nº 0058L, has conducted tests for the determination of lead and cadmium emissions, subject to system 3, and issued test reports No. 980/19 and No. 981/19 dated 2 March 2020.
6. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A2-s1, d0	EN 14411: 2016
Release of dangerous substance:		
- Cadmium	< 0,001 mg/dm ²	
- Lead	< 0,01 mg/dm ²	
Breaking strenght	> 4000 N	
Thermal shock resistance	Passed	
Durability for:		
- Interior use	Passed	
- Exterior use	Passed	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and behalf of the manufacturer:



Matilde Galende, QA Manager

Alcora, March 2020