

Storie di Milano

le pietre minerali





DECLARATION OF PERFORMANCE

<u>Nº. 001BS</u>

6 mm

- 1. Identification code of the product type: dry-pressed ceramic tiles, with water absorption $Eb \le 0.5\%$, thickness = 6 mm.
- 2. Inteded use (s): for floor ad walls, interior and exterior.
- Name and contact address of the manufacturer: BEST SURFACE S.L. Carretera de Castellón 117 y DS Foyes 5D 12110 Alcora (Castellón), Spain
- 4. System (s) of assessment and verification of constancy of performance: System 3 & 4
- Name and identification number of notified laboratory: Centro Ceramico, Laboratory nº 0058L, has conducted tests for the determination of lead and cadmium emissions, subject to system 3, and issued test reports No. 980/19 and No. 981/19 dated 2 March 2020.

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 / A1 _{FL}	
Release of dangerous substance:		
- Cadmium	< 0,001 mg/dm ²	
- Lead	< 0,01 mg/dm²	
Breaking strength	≥ 700 N	
Adhesión for cementitious adhesive,		EN 14411: 2016
type C2 S1/C2S2	>1 N/mm²	
Thermal shock resistance	Passed	
Durability for:]
- Interior use	Passed	
- Exterior use	Passed	

6. Declared performance:

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

BESTSURFACE

Best Surface Holding Srl

Via Camperio Manfredo, 14 20123 Milano - Italy Ph +39 02 58215360 Fax +39 02 58215368 P.IVA/C.F. 10463820968 REA MI-2533743 Cap. Soc. 250.000,00 Euro i.v.

Best Surface S.L.

Carretera de Castellón, 117 y DS Foyes 5 Den Partida Foyes Ferraes 12110 Alcora · Castellón NIF/VAT: B-44513752 Ph +34 964 78 45 45 Fax +34 964 78 45 00 Cap. Soc. 10.000.000 Euro i.v.

Headquarters

Via San Clemente 1 20122 Milano · Italy Ph +39 02 50020754 Fax +39 02 50020764

idylium.com



<u>Nº. 004BS</u> 6 mm MESH

- 1. Identification code of the product type: dry-pressed ceramic tiles, with water absorption $Eb \le 0.5\%$, thickness = 6 mm-mesh
- 2. Inteded use (s): for floor ad walls, interior and exterior.
- Name and contact address of the manufacturer: BEST SURFACE S.L. Carretera de Castellón 117 y DS Foyes 5D 12110 Alcora (Castellón), Spain
- 4. System (s) of assessment and verification of constancy of performance: System 3 & 4
- Name and identification number of notified laboratory: Centro Ceramico, Laboratory nº 0058L, has conducted tests for the determination of lead and cadmium emissions, subject to system 3, and issued test reports No. 980/19 and No. 981/19 dated 2 March 2020.
- 6. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A2-s1, d0	
Release of dangeruous substance:		
- Cadmium	< 0,001 mg/dm ²	EN 14411: 2016
- Lead	< 0,01 mg/dm ²	
Breaking strenght	≥ 700 N	
Thermal shock resistance	Passed	
Durability for:		
- Interior use	Passed	
- Exterior use	Passed	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and behalf of the manufacturer:

Matilde Galende, QA Manager

BESTSURFACE

Best Surface Holding Srl

Via Camperio Manfredo, 14 20123 Milano · Italy Ph +39 02 58215360 Fax +39 02 58215368 P.IVA/C.F. 10463820968 REA MI-2533743 Cap. Soc. 2<u>50.000,00 Euro j.v.</u>

Best Surface S.L.

Carretera de Castellón, 117 y DS Foyes 5 Den Partida Foyes Ferraes 12110 Alcora · Castellón NIF/VAT: B-44513752 Ph +34 964 78 45 45 Fax +34 964 78 45 00 Cap. Soc. 10.000.000 Euro i.v.

Headquarters

Via San Clemente 1 20122 Milano · Italy Ph +39 02 50020754 Fax +39 02 50020764

idylium.com