

Technical Data Sheet: 2cm

MARS Quartz 2cm Slab Size: 126" x 63"

| Physical-Chemical Properties | Test Standard | UD | Values |
|---------------------------------|--------------------|----------------------------------|------------------------------------|
| Apparent Density | UNE-EN-14617- 1 | Kg/m³ | 2.138 |
| Water Absorption | UNE-EN-14617- 1 | % | 0.05 W4 |
| Breaking Strength | UNE-EN-14617- 2 | MPa | 78.9 F ₉ |
| Impact Resistance | UNE-EN-14617- 9 | Cm/J | 121/≥11.9 |
| Abrasion Resistance | UNE-EN-14617- 4 | Mm | 27.5 A ₄ |
| Stain Resistance | ANSI Z-124.6 | | Unaffected |
| Thermal Shock Resistance | UNE-EN-14617- 6 | % Change in dynamic elastic mod. | -8.2 |
| | | % Change in mass | -0.02 |
| Thermal Conductivity | UNE-EN-12524 | W/m-K | 1.3 |
| Thermal Expansion Coefficient | UNE-EN-14617-11 | °C-1 | 45.5 ⁻ 10 ⁻⁶ |
| Slip Resistance | UNE-EN-146231 | PSRV Dry | 49 |
| | | PSRV Wet | 10 |
| Chemical Resistance | ASTM 650-04 | | Unaffected by chemicals |
| UV Resistance | | | |
| Fire Performance | AS 1530.3:1999 | Ignitability Index (0-20) | 6-8 |
| | | Spread of Flame Index (0-10) | 0-3 |
| | | Heat Developed Index (0-10) | 2-3 |
| | | Smoke Developed Index (0-10) | 6-7 |

Hilltop Surfaces 5150 Timberlea Boulevard Mississauga, Ontario Canada L4W 2S5

Ph: (905) 264-1008 Fx: (905) 264-1009 Email: info@hilltopsurfaces.com Website: www.hilltopsurfaces.com



Technical Data Sheet: 2cm

Product Composition

MARS® Quartz is manufactured with up to 90 percent high quality natural quartz crystals, high quality polyester binders, and proprietary coloring agents that are homogeneous, with uniform color throughout their thickness

Basic Limitations

MARS® Quartz is designed for interior use only, ideal for residential and commercial applications. MARS Quartz is a solid, non-porous, highly durable surface and resistant to scratching, staining, and water absorption and is virtually maintenance free.

All stone surfaces, including quartz made from natural quartz crystals, is not chip proof. Objects hitting edges especially in areas like around the sink or appliances may cause chipping. The surfaces can also be damaged by a sudden change in temperature and may not withstand the direct transfer of heat from pots and pans or other heat-producing items. Please use trivets or boards to protect your surfaces before setting any hot items down on the surface.

Cleaning Guidelines

Cleaning MARS Quartz is easy! Use a soft, non-abrasive cotton cloth and warm water. If needed, a mild, allpurpose soap can be used for larger messes. Do not use any physical or chemical abrasives like scrubbing pads or bleach.